ORTHO

ORTHOPEDIC + TECHNICAL

ORTHOTECH

Innovative Manufacturer Specialized in Orthopedics

CATALOG LIST & BODY SIMULATION

Pin & Wire, Double Threaded Wire	04
External Fixator, Art Band Pin	05
Cannulated Compression Screw(CCS)	06
Variable Pitch Screw(VPS)	07
Snap Off Screw	08
Space Screw	09
Ligament & ACL Screw	10
Mini Locking Plate	11
Distal Radius Plate, Mid shaft Plate	12
Small Plate, Calcaneal Locking Plate, Distal Fibular Locking Plate	13
Clavicle Locking Plate, Proximal Humerus Locking Plate	14
Large Locking Plate	15
Compression Hip Screw(CHS)	16
BARO-FIX HTO Plate, HTO T DTL Locking Plate	17
Proximal Femur Nail	18
Tibia & Femur Nail	19
Cable & Grip Plate	20
Spinal System - Pedicle Screw, Peek Cage	21
Customized Products, ETC	22
Broken Screw Removal Set, Location	23

SCREW

Stand Alone Screw

- Variable Pitch Screw
- Cannulated Compression Screw

Cage & Pedicle Screw

- PLIF
- Pedicle Screw

Space Screw

- Ø2.0 / Ø2.5 / Ø3.5 / Ø4.0

Snap Off Screw

- Ø2.0 / Ø2.7

ETC

- Broken Screw Removal Set
- Vacuum Mixer
- Total Care Pack

Shoulder & Elbow

Mid Shaft Plate

Clavicle Plate

Proximal Humerus Plate

Distal Humerus Plate

Leg

Proximal Tibia Medial Plate
Lateral Locking Plate

Distal Tibia Medial Plate
Lateral Locking Plate

Distal Femur Plate

Locking Compression Plate

Tibial Nail

Femoral Nail

Hip

Grip Plate & Cable

Proximal Femur Nail

Compression Hip Screw
& Trochanter Plate



Hand & Wrist

Mini Plate

Distal Radius Plate

Wrist External Fixator

Small External Fixator

Double Threaded Wire

Knee

BARO-FIX HTO Plate

HTO T Plate


ACL Screw
& Ligament Screw

Art Band Pin

Foot & Ankle

Distal Fibular Plate

Calcaneal Locking Plate


Small Plate

Pin & Wire

■ Wrist/Small Half Pin Cortical Type

■ Half Pin Cortical - Middle

■ Half Pin Cancellous Type

■ Half Pin Cortical Type

■ Half Pin Ilizarov Cortical

■ Phalanx Pin

Type	Ø0.8	Ø1.0	Ø1.2	Ø1.4	Ø1.6
Non Threaded	ETN08190	ETN10190	ETN12190	ETN14190	ETN16190

■ Kirschner Wire

Point Style	Ø0.8	Ø0.9	Ø1.0	Ø1.1	Ø1.2	Ø1.4	Ø1.6	Ø1.8
Trocar	E301		E302		E303	E304	E305	E306
Diamond	E311	E317	E312	E318	E313	E314	E315	E316

■ Steinmann Pin

Point Style	Ø2.0	Ø2.2	Ø2.3	Ø2.4	Ø2.6	Ø2.7	Ø2.8	Ø3.0	Ø3.1	Ø3.2	Ø3.5	Ø3.9	Ø4.0
Trocar	E401		E402			E403			E404		E405	E406	
Diamond	E411	E417	E412	E418	E419	E413	E420	E421	E414	E423	E415	E416	E422

MFDS.Lisence#
00-197 : : : Half Pin(ST)
02-360 : : : Half Pin(Ti)
00-197 : : : Phalanx Pin
02-434 : : : Kirschner Wire
02-436 : : : Steinmann Pin

Material
Stainless Steel (ASTM F138) : : : Half Pin(ST)
Titanium (ASTM F136) : : : Half Pin(Ti)
Stainless Steel (ASTM F138) : : : Phalanx Pin
Stainless Steel (ASTM F138) : : : Kirschner Wire
Stainless Steel (ASTM F138) : : : Steinmann Pin

EDI code
C1605128 : : : Cortical Half Pin(ST)
C1605028 : : : Cancellous Half Pin(ST)
C1606128 : : : Cortical Half Pin(Ti)
C1605228 : : : Phalanx Pin
D0005028 : : : Kirschner Wire
C4005028 : : : Steinmann Pin

Description	Cat.No	Core Diameter	Body Diameter	Thread Length	Total Length	Picth
Wrist/Small Half Pin Cortical Type	E101	2.0	2.0	12	45	0.8
	E102	2.0	2.0	12	75	0.8
	E103	2.2	2.3	12	50	0.8
	E104	2.2	2.3	15	65	0.8
	E105	2.2	2.5	15	75	0.8
	E106	2.5	3.2	15	70	1.0
	E107	3.0	3.2	20	80	1.0
Half Pin Cortical Type	E110	4.0	6.0	20	80	1.25
	E111	4.0	6.0	25	100	1.25
	E112	4.0	6.0	30	120	1.25
	E113	4.0	6.0	35	140	1.25
	E114	5.0	6.0	30	130	1.5
	E115	5.0	6.0	40	150	1.5
	E116	5.0	6.0	50	170	1.5
Half Pin Cancellous Type	E117	5.0	6.0	40	130	3.0
	E118	5.0	6.0	50	150	3.0
	E119	5.0	6.0	60	180	3.0
Half Pin Cortical Type Titanium	E171	2.5	3.2	15	70	1.0
	E172	3.0	3.2	20	80	1.0
	E173	4.0	5.0	25	120	1.25
	E174	4.0	6.0	30	120	1.25
	E175	5.0	6.0	40	150	1.5
	E176	5.0	6.0	50	170	1.5
Half Pin Ilizarov Cortical Type	E151	4.0	5.0	25	120	1.25
	E152	5.0	5.0	30	130	1.5
	E153	5.0	5.0	35	150	1.5
	E154	5.0	5.0	40	170	1.5
Half Pin-Cor.Middle	E120	5.0	5.0	50.5	200	1.5

Double Threaded Wire

MFDS.Lisence# 18-488
Material Stainless Steel (ASTM F138)
EDI code C4004028



Cat.No	Spec
EBD08190S	Ø0.8 x 190mm
EBD10190S	Ø1.0 x 190mm
EBD12190S	Ø1.2 x 190mm
EBD14190S	Ø1.4 x 190mm
EBD16190S	Ø1.6 x 190mm
EBD18190S	Ø1.8 x 190mm
EBD20190S	Ø2.0 x 190mm

Features of Double Threaded Wire

1. Double sided design allows you to choose between Threaded and Non Threaded types
2. Relieve pain and discomfort by tightening the ball on the edge

External Fixator

■ Pelvic External Fixator

■ Small External Fixator

■ Wrist External Fixator

Art Band Pin

MFDS.Lisence#	18-772
Material	Stainless Steel (ASTM F138)
EDI code	BC4100AS



■ Art Band Pin – Double Type

Cat.No	A	B	C	D
E144	120	70	1.6	1.7
E148	140	70	2.0	2.1

■ Snapper

Cat.No	A	B	C
IS80-02	112	Ø8.0	Ø2.2

Cannulated Compression Screw (CCS)

MFDS.Lisence#	21- 847
Material	Titanium (ASTM F136)
EDI code	C6411628 : : : Screw D1211128 : : : Washer



Description	Length(mm)	Cat.No
Ø4.0 CCS	5x12	SU40012D
	5x14	SU40014D
	5x16	SU40016D
	6x18	SU40018D
	6x20	SU40020D
	8x22	SU40022D
	8x24	SU40024D
	10x26	SU40026D
	10x28	SU40028D
	12x30	SU40030D
	12x35	SU40035D
	14x40	SU40040D
	14x45	SU40045D
	16x50	SU40050D
	16x55	SU40055D
	16x60	SU40060D
	16x65	SU40065D
	16x70	SU40070D
	Washer	SU40D

Description	Length(mm)	Cat.No
Ø5.0 CCS	12x24	SU50024D
	12x26	SU50026D
	14x28	SU50028D
	14x30	SU50030D
	16x34	SU50034D
	16x38	SU50038D
	20x42	SU50042D
	20x46	SU50046D
	20x50	SU50050D
	20x55	SU50055D
	20x60	SU50060D
	20x65	SU50065D
	20x70	SU50070D
	Washer	SU50D

Description	Length(mm)	Cat.No
Ø6.5 CCS	16x35	SU65035D
	20x40	SU65040D
	20x45	SU65045D
	20x50	SU65050D
	20x55	SU65055D
	20x60	SU65060D
	20x65	SU65065D
	20x70	SU65070D
	20x75	SU65075D
	20x80	SU65080D
	20x85	SU65085D
	20x90	SU65090D
	20x95	SU65095D
	20x100	SU65100D
	20x105	SU65105D
	20x110	SU65110D
	Washer	SU65D

Variable Pitch Screw (VPS)

MFDS.Lisence#	17-415
Material	Titanium (ASTM F136)
EDI code	C6411328







Description	Length(mm)	Cat.No
Ø3.2 VPS	16	S1121
	18	S1122
	20	S1123
	22	S1124
	24	S1125
	26	S1126
	28	S1127
	30	S1128
	35	S1129
	40	S1130

Description	Length(mm)	Cat.No
Ø4.0 VPS	16	S1221
	18	S1222
	20	S1223
	22	S1224
	24	S1225
	26	S1226
	28	S1227
	30	S1228
	35	S1229
	40	S1230
	45	S1231
	50	S1232

Description	Length(mm)	Cat.No
Ø5.0/6.0 VPS	35	S1321
	40	S1322
	45	S1323
	50	S1324
	55	S1325
	60	S1326
	65	S1327
	70	S1328
	75	S1329
	80	S1330

Ø3.2 / Ø4.0

Ø5.0 /6.0

Self Tapping

Snap Off Screw

MFDS.Lisence#	21-108
Material	Titanium (ASTM F136)
EDI code	C6421296





Description	Length(mm)	Cat.No
Ø2.0 Snap Off Screw	10	SO2010D
	11	SO2011D
	12	SO2012D
	13	SO2013D
	14	SO2014D
	15	SO2015D
	16	SO2016D
	17	SO2017D
	18	SO2018D
	19	SO2019D
	20	SO2020D

Description	Length(mm)	Cat.No
Ø2.7 Snap Off Screw	14	SO2714D
	16	SO2716D
	18	SO2718D
	20	SO2720D
	22	SO2722D
	24	SO2724D

Features of Snap Off Screw

1. Safe and reliable mechanical strength by using biocompatible raw materials
2. Can independently be used in osteotomy and fractures
3. Wide range of options in screw lengths
4. Strong retention even in thin bones
5. No drilling necessary
6. Selective use of handpiece or driver depending on the situation

Space Screw

MFDS.Lisence#	18-500 : : : Mini Plate 13-1611 : : : Radius Plate, Small Plate 19-35 : : : Large Plate Tibia, Large Plate Femur
Material	Titanium (ASTM F136)
EDI code	BD1100AS : : : Radius, Small Plate System BD1101AS : : : Large Plate System



■ Mini

■ Radius

■ Small

■ Large Tibia

■ Large Femur

Height(mm)	Ø2.0 Mini	Ø2.5 Radius	Ø3.5 Small	Ø3.5 Tibia	Ø4.5 Femur	Ø5.0 Femur
0.0	●	●	●	●	●	●
0.5	●	●	●	●	●	●
1.0	●	●	●	●	●	●
1.5	●	●	●	●	●	●
2.0	●	●	●	●	●	●





Features of Space Screw

1. Increase plate load bearing strength
2. Helps better blood flow to the periosteum
3. Wide range of options
4. Easy storage
5. Convenient use through pick-up

Ligament & ACL Screw

MFDS.Lisence#	09-1088 : : : Ligament Bone Screw & Washer 19-805 : : : Suture Washer, Suture Washer Spiked
Material	Titanium (ASTM F136) : : : Screw Titanium (ASTM F67) : : : Washer
EDI code	C2021052 : : : Ligament Bone Screw C2300152 : : : Cannulated Bone Screw C2301080 : : : Ligament Washer



Description	Length(mm)	Bone Screw Cat.No	Bone Screw Wide Head	Cannulated Bone Screw Cat.No	Cannulated Bone Screw Wide Head	Ligament Spiked Washer	Ligament Spiked Washer Cat.No
Ø6.5	30	S0103	S0153	S0113	S0163D	Foot	S0141D
	35	S0104	S0154	S0114	S0164D	Point O	S0142D
	40	S0105	S0155	S0115	S0165D	Point X	S0143D
	45	S0106	S0156	S0116	S0166D		
	50	S0107	S0157	S0117	S0167D		
	55	S0108	S0158	S0118	S0168D		



MFDS.Lisence#	17-389 : : : Cannulated Interference Screw(Peek) 09-1089 : : : Cannulated Interference Screw(Ti)
Material	PEEK (ASTM F2026) : : : Screw Titanium (ASTM F136) : : : Screw
EDI code	C2303028 : : : Cannulated Interference Screw(Peek) C2300052 : : : Cannulated Interference Screw(Ti)

Description	Length(mm)	Diagonal Type Cat.No	Round Type Cat.No	Peek Type Cat.No
Ø7	20	G106	G126	P126
	25	G107	G127	P127
	30	G108	G128	P128
Ø8	20	G109	G129	P129
	25	G110	G130	P130
	30	G111	G131	P131
Ø9	20	G112	G132	P132
	25	G113	G133	P133
	30	G114	G134	P134

Mini Locking Plate

MFDS.Lisence#	18-501
Material	Titanium (ASTM F67)
EDI code	C5491180

Y Type

Hole	Cat.NO
6Hole	P1306
7Hole	P1307
8Hole	P1308

L Type

Hole	Left	Right
6Hole	P11L6	P11R6
7Hole	P11L7	P11R7
8Hole	P11L8	P11R8

Straight Type

Hole	Cat.NO
6Hole	P1006
7Hole	P1007
8Hole	P1008
9Hole	P1009
14Hole	P1014

T Type

Hole	Cat.NO
7Hole	P1207
8Hole	P1208
10Hole	P1210



Compatible With	Length
Ø2.0mm Cortical Screw	6 ~ 20mm
Ø2.0mm Locking Cortical Screw	6 ~ 20mm (Increase by : 1mm)

Distal Radius Plate

MFDS.Lisence#	13-1611
Material	Titanium (ASTM F67)
EDI code	C5475080

Description	Spec	Cat.No
Distal Radius Small Plate	1Hole - Right	P2422
	2Hole - Right	P2424
	3Hole - Right	P2426
	1Hole - Left	P2421
	2Hole - Left	P2423
	3Hole - Left	P2425
Distal Radius Narrow Plate	1Hole - Right	P2412
	2Hole - Right	P2414
	3Hole - Right	P2416
	1Hole - Left	P2411
	2Hole - Left	P2413
	3Hole - Left	P2415
Distal Radius Broad Plate	1Hole - Right	P2402
	2Hole - Right	P2404
	3Hole - Right	P2406
	1Hole - Left	P2401
	2Hole - Left	P2403
	3Hole - Left	P2405



Compatible With	Length
Ø2.5mm Cortical Screw	6 ~ 30mm
Ø2.5mm Locking Cortical Screw	6 ~ 30mm
Ø2.5mm Cortical Screw – Can. Type	6 ~ 30mm (By : 2mm)

Mid Shaft Plate

MFDS.Lisence#	18-783
Material	Titanium (ASTM F67)
EDI code	C5475280

Compatible With	Length
Ø3.5mm Cortical Screw	8 ~ 50mm
Ø3.5mm Locking Cortical Screw	8 ~ 50mm
Ø4.0mm Cancellous Screw(Half/Full)	10 ~ 70mm
Ø4.0mm Locking Screw – Can. Type	8 ~ 70mm (By : 2mm)

■ Mid Shaft Plate

Spec	Cat.No
8Hole	P2501
9Hole	P2502
13Hole	P2503
15Hole	P2504

Small Plate

MFDS.Lisence#	21-725
Material	Titanium (ASTM F67)
EDI code	C5463280 : : : Dynamic Compression Plate C5461280 : : : One Third Tubular Locking Plate C5460280 : : : Reconstruction Locking Plate

Description	Spec	Cat.No
Dynamic Compression Plate	4Hole	P0301
	5Hole	P0302
	6Hole	P0303
	7Hole	P0304
	8Hole	P0305
One Third Tubular Locking Plate	4Hole	P0311
	5Hole	P0312
	6Hole	P0313
	7Hole	P0314
	8Hole	P0315
Reconstruction Locking Plate	4Hole	P0321
	5Hole	P0322
	6Hole	P0323
	7Hole	P0324
	8Hole	P0325
	9Hole	P0326
	10Hole	P0327

■ Dynamic Compression Plate

■ One Third Tubular Locking Plate

■ Reconstruction Locking Plate

Calcaneal Locking Plate

Spec	Cat.No
Small (12H)	P4701
Medium (16H)	P4702
Large (19H)	P4703



Can be used in both sides

MFDS.Lisence#	13-1611
Material	Titanium (ASTM F67)
EDI code	C5467480

Distal Fibular Locking Plate



Description	Spec	Cat.No
Distal Fibular Broad Plate	7 Hole	P4601
	8 Hole	P4602
	9 Hole	P4603
	10 Hole	P4604
	11 Hole	P4605
	12 Hole	P4606
	13 Hole	P4607
Distal Fibular Narrow Plate	7 Hole	P4611
	8 Hole	P4612
	9 Hole	P4613
	10 Hole	P4614
	11 Hole	P4615
	12 Hole	P4616
	13 Hole	P4617
Distal Fibular Hook Plate	6 Hole	P4621
	7 Hole	P4622
	8 Hole	P4623
	9 Hole	P4624

Compatible With	Length
Ø3.5mm Cortical Screw	8 ~ 50mm
Ø3.5mm Locking Cortical Screw	8 ~ 50mm
Ø4.0mm Cancellous Screw(Half/Full)	10 ~ 70mm
Ø4.0mm Locking Screw – Can. Type	8 ~ 70mm (By : 2mm)

MFDS.Lisence#	13-1611
Material	Titanium (ASTM F67)
EDI code	C5430080

Clavicle Locking Plate

MFDS.Lisence#	17-387
Material	Titanium (ASTM F67)
EDI code	C5478128 : : : Clavicle Shaft Plate C5478228 : : : Clavicle Hook Plate C5478328 : : : Clavicle End Plate

Spec	Left	Right
6Hole A	P2041	P2042
6Hole B	P2043	P2044
7Hole A	P2045	P2046
7Hole B	P2047	P2048
8Hole	P2049	P2050
9Hole	P2051	P2052
10Hole	P2053	P2054

Spec	Height(mm)	Left	Right
6Hole	12	P2001	P2002
	15	P2003	P2004
	18	P2005	P2006
7Hole	12	P2007	P2008
	15	P2009	P2010
	18	P2011	P2012
8Hole	12	P2013	P2014
	15	P2015	P2016
	18	P2017	P2018



Spec	Left	Right
6Hole	P2021	P2022
7Hole	P2023	P2024
8Hole	P2025	P2026



Proximal Humerus Locking Plate



Compatible With	Length
Ø3.5mm Cortical Screw	8 ~ 50mm
Ø3.5mm Locking Cortical Screw	8 ~ 50mm
Ø4.0mm Cancellous Screw(Half/Full)	10 ~ 70mm
Ø4.0mm Locking Screw – Can. Type	8 ~ 70mm (By : 2mm)

MFDS.Lisence#	13-1611
Material	Titanium (ASTM F67)
EDI code	C5475080

Spec	Cat.No
2Hole	P2101
3Hole	P2102
4Hole	P2103
5Hole	P2104

Spec	Cat.No
2Hole	P2111
3Hole	P2112
4Hole	P2113
5Hole	P2114

Large Locking Plate

MFDS.Lisence#	18-783
Material	Titanium (ASTM F67)
EDI code	C5430280



■ Distal Tibia Lateral Locking Plate

Spec	Left	Right
4Hole	P45L04	P45R04
5Hole	P45L05	P45R05
7Hole	P45L07	P45R07
9Hole	P45L09	P45R09
12Hole	P45L12	P45R12
15Hole	P45L15	P45R15

■ Distal Tibia Medial Locking Plate

Spec	Left	Right
4Hole	P44L04	P44R04
5Hole	P44L05	P44R05
7Hole	P44L07	P44R07
9Hole	P44L09	P44R09
12Hole	P44L12	P44R12
16Hole	P44L16	P44R16

■ Proximal Tibia Lateral Locking Plate

Spec	Left	Right
4Hole	P43L04	P43R04
5Hole	P43L05	P43R05
7Hole	P43L07	P43R07
9Hole	P43L09	P43R09
12Hole	P43L12	P43R12
16Hole	P43L16	P43R16



■ Proximal Tibia Medial Plate

Spec	Left	Right
2Hole	P42L04	P42R04
4Hole	P42L06	P42R06
6Hole	P42L08	P42R08
8Hole	P42L10	P42R10



Features of Large Plate

1. Low profile
2. Blood circulation
3. Sharp Entry enables MIS surgery
4. Faster Recovery

Compatible With	Length
Ø4.5mm Cortical Screw	20 ~ 80mm
Ø4.5mm Locking Cortical Screw	20 ~ 80mm
Ø5.0mm Locking Cortical Screw – Can. Type	26 ~ 80mm (By : 2mm)

* Tibia uses same specification with 3.5mm Locking Cortical Screw, and 4.0mm Locking Cortical Screw – Can. Type

■ Distal Femur Locking Plate

Spec	Left	Right
4Hole	P41L04	P41R04
5Hole	P41L05	P41R05
7Hole	P41L07	P41R07
9Hole	P41L09	P41R09
12Hole	P41L12	P41R12
15Hole	P41L15	P41R15



■ Locking Compression Plate – Narrow B Type

Spec	Narrow
98mm x 2H x 4H	P49B06
114mm x 2H x 5H	P49B07
130mm x 2H x 6H	P49B08
146mm x 2H x 7H	P49B09
162mm x 2H x 8H	P49B10
178mm x 2H x 9H	P49B11
194mm x 2H x 10H	P49B12S
210mm x 4H x 8H	P49B12L
226mm x 4H x 10H	P49B14

■ Locking Compression Plate – Broad B Type

■ Curved Locking Compression Plate – Broad Locky Type

Spec	Broad	Curved
122mm x 2H x 4H	P48B06	P48C06
138mm x 2H x 6H	P48B08S	P48C08S
154mm x 2H x 6H	P48B08L	P48C08L
170mm x 2H x 8H	P48B10S	P48C10S
186mm x 2H x 8H	P48B10L	P48C10L
218mm x 4H x 8H	P48B12	P48C12
250mm x 4H x 10H	P48B14	P48C14
282mm x 4H x 12H	P48B16	P48C16

Compression Hip Screw (CHS)

MFDS.Lisence#	07-188 : : : CHS Plate
Material	Titanium(ASTM F67) : : : CHS Plate, Trochanter Stabilizing Plate Titanium(ASTM F136) : : : Lag screw, Compression Screw
EDI code	C5451080 : : : CHS Plate, Lag/Compression Screw C5452080 : : : TSP Plate

■ CHS Dynamic Compression Plate Head Long Type

Hole	Cat.No
1Hole	3000L1
2Hole	3000L2
3Hole	P3001
4Hole	P3002
5Hole	P3003
6Hole	P3004
8Hole	P3005



■ CHS Dynamic Compression Plate Head Short Type

Hole	Cat.No
1Hole	3000S1
2Hole	3000S2
3Hole	P3007
4Hole	P3008
5Hole	P3009
6Hole	P3010

■ Trochanter Stabilizing Plate(TSP)

Cat.No
P3028

■ Lag Screw

Length(mm)	Cat.No
50	P3011
55	P3012
60	P3013
65	P3014
70	P3015
75	P3016
80	P3017
85	P3018
90	P3019
95	P3020
100	P3021
105	P3022
110	P3023

■ Compression Screw

Length(mm)	Cat.No
26	P3024
31	P3025
36	P3026
41	P3027

Compatible With	Length
Ø4.5mm Cortical Screw	16 ~ 100mm (By : 2mm)
Ø6.5mm Cancellous Screw(16mm)	25 ~ 100mm (By : 5mm)
Ø6.5mm Cancellous Screw(32mm)	45 ~ 100mm (By : 5mm)
Ø6.5mm Cancellous Screw(Full)	25 ~ 100mm (By : 5mm)
Ø4.5mm Malleolar Screw	25 ~ 70mm (By : 5mm)

Baro - Fix®
HTO Plate

MFDS.Lisence#	13-1987
Material	Titanium (ASTM F67) : : : Plate, Block, Screw
EDI code	C5430180 : : : Plate C6411028 : : : Cortical Screw C6400080 : : : Locking Screw C6411428 : : : Cannulated Screw



Description	Spec	Cat.No
Baro-Fix Plate	3 Hole	P50L03
		P50R03
	4 Hole	P50L04
		P50R04
HTO T Locking Plate	3 Hole	P5015
	4 Hole	P5016



■ Wedge Spiked Block

Description	Size	Cat.No
Wedge Spiked Block 1Hole	5T (4.5 - 5.5)	P5026
	6T (5.5 - 6.5)	P5027
	7T (6.5 - 7.5)	P5028
	8T (7.5 - 8.5)	P5029
	9T (8.5 - 9.5)	P5030
	10T (9.5 - 10.5)	P5031
	11T (10.5 - 11.5)	P5032
	12T (11.5 - 12.5)	P5033
	13T (12.5 - 13.5)	P5034
	14T (13.5 - 14.5)	P5035
	15T (14.5 - 15.5)	P5036
Wedge Spiked Block 3Hole	5T (4.5 - 5.5)	P50B05
	6T (5.5 - 6.5)	P50B06
	7T(6.5 - 7.5)	P50B07
	8T (7.5 - 8.5)	P50B08
	9T (8.5 - 9.5)	P50B09
	10T (9.5 - 10.5)	P50B10
	11T (10.5 - 11.5)	P50B11
	12T (11.5 - 12.5)	P50B12
	13T (12.5 - 13.5)	P50B13
	14T (13.5 - 14.5)	P50B14
	15T (14.5 - 15.5)	P50B15

DTL HTO T
Locking Plate

Compatible With	Length
Ø4.5mm Cortical Screw	26 ~ 70mm
Ø5.0mm Locking Cortical Screw	26 ~ 70mm
Ø5.0mm Locking Cortical Screw – Can. Type	26 ~ 70mm (By : 2mm)
Wedge Spiked Block Bolt	10.8mm

* Both Baro-Fix® and DTL type uses the same Screw and Wedge Spiked Block

HTO Plate

1. Choice of left, right and T plate
2. High bone contact stability due to anatomical design
3. High satisfaction when suturing MCL, Harmstring osteoporosis with double hole function
4. Excellent safety with Angular Stability
5. Provide more options to users as the Block 1 hole + 3 holes can be used together

Proximal Femur Nail

MFDS.Lisence#	13-1608
Material	Titanium (ASTM F136)
EDI code	C3115080 : : : PF Nail Set

Spec	Cat.No
12.5 x 7	N5471
14 x 12	N5472
14 x 17	N5473
14 x 22	N5474

Description	Spec	Cat.No
Inner Screw	9 x 29	N5481
Final Inner Screw	9 x 29	N5482

Description	Length(mm)	PF - Nail 120°	PF - Nail 125°	PF - Nail 130°	PF - Nail - Static Hole Type 120°	PF - Nail - Static Hole Type 125°	PF - Nail - Static Hole Type 130°
Ø9	170	N5001	N5031	N5061	N5001AD	N5031AD	N5061AD
	200	N5002	N5032	N5062	N5002AD	N5032AD	N5062AD
	230	N5003	N5033	N5063	N5003AD	N5033AD	N5063AD
Ø10	170	N5004	N5034	N5064	N5004A	N5034A	N5064A
	200	N5005	N5035	N5065	N5005A	N5035A	N5065A
	230	N5006	N5036	N5066	N5006A	N5036A	N5066A
Ø11	170	N5007	N5037	N5067	N5007A	N5037A	N5067A
	200	N5008	N5038	N5068	N5008A	N5038A	N5068A
	230	N5009	N5039	N5069	N5009A	N5039A	N5069A
Ø12	170	N5010	N5040	N5070	N5010A	N5040A	N5070A
	200	N5011	N5041	N5071	N5011A	N5041A	N5071A
	230	N5012	N5042	N5072	N5012A	N5042A	N5072A

Length(mm)	Screw Type Cat.No	B Type Cat.No
70	N5401	NLSB70
75	N5402	NLSB75
80	N5403	NLSB80
85	N5404	NLSB85
90	N5405	NLSB90
95	N5406	NLSB95
100	N5407	NLSB100
105	N5408	NLSB105
110	N5409	NLSB110

Length(mm)	Blade Type Cat.No	B Type Cat.No
70	N5421	NLBB70
75	N5422	NLBB75
80	N5423	NLBB80
85	N5424	NLBB85
90	N5425	NLBB90
95	N5426	NLBB95
100	N5427	NLBB100
105	N5428	NLBB105
110	N5429	NLBB110



Tibia & Femur Nail

MFDS.Lisence#	13-1608
Material	Titanium (ASTM F136)
EDI code	C3112180 : : : Tibia Type Set C3111180 : : : Femoral Type C3191180 : : : Locking Screw

Spec	Cat.No
L-0	N0301
L-5	N0302
L-10	N0303

Length(mm)	Ø8		Ø9		Ø10	Ø11	Ø12
	Unreaming	Reaming	Unreaming	Reaming	Reaming	Reaming	Reaming
270	N7501	N7501R	N7511	N7511R	N7521	N7531	N7541
285	N7502	N7502R	N7512	N7512R	N7522	N7532	N7542
300	N7503	N7503R	N7513	N7513R	N7523	N7533	N7543
315	N7504	N7504R	N7514	N7514R	N7524	N7534	N7544
330	N7505	N7505R	N7515	N7515R	N7525	N7535	N7545
345	N7506	N7506R	N7516	N7516R	N7526	N7536	N7546



Compatible With	Length
Ø5.0mm Locking Screw	25 ~ 80mm
Ø6.0mm Locking Screw	25 ~ 70mm (By : 5mm)

Length(mm)	Ø10	Ø11	Ø12	Ø13
320	N5501	N5511	N5521	N5531
340	N5502	N5512	N5522	N5532
360	N5503	N5513	N5523	N5533
380	N5504	N5514	N5524	N5534
400	N5505	N5515	N5525	N5535
420	N5506	N5516	N5526	N5536
440	N5507	N5517	N5527	N5537

Features of Tibia & Femur Nail

1. Nail suitable for long fractures
2. Medical titanium supporting safety

Cable & Grip Plate

MFDS.Lisence#	17-643
Material	Stainless Steel (ASTM F138)
EDI code	E1304083 : : : Cable E1303083 : : : Cable Sleeve E1313083 : : : Grip Plate Long E1314083 : : : Grip Plate Short E1300083 : : : Cable&Sleeve Set E1311083 : : : Cable&Grip Plate Set (Short) E1312083 : : : Cable&Grip Plate Set (Long)

■ 2.0 Cable

ASTM F138 (STS –316LVM)
Cable Zoom (7x7 Twist Coil Type)



■ 2.0 Cable Sleeve

Product	Cat.No	Spec
Sleeve	E562	Cable Sleeve - Spiked Type
	E563	Sleeve Connecter - Large Head Type (4.5/6.5 screw)
	E564	Sleeve Connecter - Small Head Type (3.5/4.0 screw)
	E565	Sleeve Connecter - Small Basic Type (2.5hex)
	E566	Sleeve Connecter - Large Basic Type (3.5hex)
	E567	Cable Sleeve
Set	ES56775	Cable +Sleeve Set

Product	Cat.No	Size
Grip Plate	E571	Short
	E572	1Hole
	E573	3Hole
Cable	E557	2.0 x 750mm



Spinal System - Pedicle Screw

MFDS.Lisence#	19-843
Material	Titanium (ASTM F136)
EDI code	F0018383 : : : Screw Set F0016483 : : : Rod F0019383 : : : Cross Link





Product	Diameter	Length
Mono Screw - Standard Type Poly Screw - Standard Type Poly Screw - Reduction Type	Ø4.0 ~ 8.0	20 ~ 60mm (By : 5mm)

■ Rod

Product	Spec	
Straight/Curved	Ø6.0	40 ~ 600mm

■ Set Screw(Ø6.0)

Cat.No
LNSS105



■ Cross Link

Cat.No	Spec
LNCL6232	29 ~ 32mm
LNCL6237	31 ~ 37mm
LNCL6247	35 ~ 47mm
LNCL6265	43 ~ 65mm
LNCL6299	62 ~ 99mm

Peek Cage

■ PLIF
(Posterior Lumbar Interbody Fusion)

Depth	Width	Hight	Angle 0°	Angle 4°	Angle 8°
25	11	8	HPLP0008U	HPLP0408U	HPLP0808U
		9	HPLP0009U	HPLP0409U	HPLP0809U
		10	HPLP0010U	HPLP0410U	HPLP0810U
		11	HPLP0011U	HPLP0411U	HPLP0811U
		12	HPLP0012U	HPLP0412U	HPLP0812U
		13	HPLP0013U	HPLP0413U	HPLP0813U
		14	HPLP0014U	HPLP0414U	HPLP0814U
		15	HPLP0015U	HPLP0415U	HPLP0815U
		16	HPLP0016U	HPLP0416U	HPLP0816U

MFDS.Lisence#	20-133
Material	PEEK (ASTM F2026)
EDI code	F0101083

Customized Products

■ Radiolucent Hohmann

ETC

Colla Shield



Hit Warming

Double Arm Needle

Easy Band2

Stokinet

Radi Set

Vacuum Mixer

Medical Underwear

Total Care Pack

01 Tissue supplement, collagen
02 Medical Supplies
03 Polyester Suture
04 Pressure Bandage
05 Pressure Bandage
06 Skin Protector
07 Medical Cement Mixer
08 Splint
09 Splint, extremity, inflatable

Broken Set

■ Broken Screw Removal Set Case

Main instrument for broken removal

Screw Driver / Hex

Screw Driver / Cross

Screw Driver / Torx

Screw Driver / Minus



Sonical Extraction Screw

Extraction Screw

Broken Screw Extractor

Broken Drill Bit

Location

Head Office & Factory
78 Yuram-ro, Dong-gu, Daegu, 41059,
Rep. of Korea

Seoul Branch
#1001 ITECO Green Zone, 150 Jojeong-daero, Hanam-si, Gyeonggi-do ,
Rep. of Korea

Human R&D Center
100-4 Cheombok-ro, Dong-gu, Daegu,
Rep. of Korea

www.orthotech.co.kr

ORTHOTECH

Copyright © ORTHOTECH All Rights Reserved.

HEAD OFFICE

Factory

Add › 78 Yuram-ro, Dong-gu, Daegu, 41059, Rep of Korea

Tel › +82-53-314-7016

Fax › +82-53-314-7017

Mail › orthotech@orthotech.co.kr

SEOUL BRANCH

Add › #1001 ITECO Green Zone, 150 Jojeong-daero, Hanam-si,Gyeonggi-do , Republic of Korea

Tel › +82-70-5080-5669

Fax › +82-53-314-7017

HUMAN R&D CENTER

Add › 100-4 Cheombok-ro, Dong-gu, Daegu, Rep. of Korea

Tel › +82-53-314-7016 ~5

OTBR-51(6)_2023.09.25